



材料Material

原料Raw material: PA6T, (UL 94V-0)

相关材料Related Material: Phosphor Bronze

表面涂层Surface Coating: Gold Over Nickel

规格Specification

额定电流Current rating: 1AMP

耐压Dielectric Withstanding Voltage: 500v Ac Min

绝缘电阻Insulation Resistance: 1000MΩ min

接触电阻Contact resistance: 30MΩ Max

工作温度Operating Temperature: -45℃~+105℃

Order Information:

[03] [XX] [X] [XX] [X] [XX]

NO. of Pins Per Row 1-50	Connector Type I= Straight L= Right Angle S= S.M.T	Contact Plating 100=G/F 0.8u" 101=1u" 102=3u" 103=5u"	Material Option A: BK-PBT B: BK-PA66 C: BK-PA6T D: BK-PA46 E: BK-LCP F: Special	Spacing 01=2.54mm 02=2.0mm 03=1.27mm
-----------------------------	---	---	---	---

Unless Otherwise Specified			1.27mm Female Header , Dual Row , S.M.T			上海洲日电子有限公司						
Dimension	Tolerance		Drawing Number 20140718 A/0			Shanghai Zhouri Electronics CO.,LTD 上海康司玛电子设备进出口有限公司						
	Decimal	Angle										
X.	±0.3	±5°	Version Number ZR20140718-PM-05			Shanghai KangSiMa Eletronic Equipment import and export Co.,LTD						
X.X	±0.2	±3°										
X.XX	±0.15		Designed	Ma Chao		REV	A	Scale	1:1	Unit	mm	A4
Checked	Li zhen		Approved	Fan Hao Hua		The Third Angle Projection			Sheet Of Pages			