



材料Material

原料Insulator: PA6T,(UL 94V-0)

相关材料Related Material: Brass

表面涂层Surface Coating: Gold Over Nickel

规格Specification

额定电流Current rating: 1AMP

耐压Dielectric Withstanding Voltage: 500v Ac Min

绝缘电阻Insulation Resistance: 1000MΩ min

接触电阻Contact resistance: 30MΩ Max

工作温度Operating Temperature: -45℃~+105℃

Order Information:

02	X	XX	X	XX/XXX	XX	X	XX
Plastics Height 1.H=2.54mm 2.H=2.0mm 3.H=1.0mm	No.of Pins Per Row 1X40 1-40	Connector Type I=Straight L=Right Angle S=S.M.T	Pin Length XX=C+D+H XXX=C+D+H+E	Contact Plating 100=G/F 0.8u" 101=1u" 102=3u" 103=5u"	Insulator Material Option A: BK-PBT B: BK-PA66 C: BK-PA6T D: BK-PA46 E: BK-LCP F: Special	Space 01=2.54mm 02=2.0mm 03=1.27mm	

P. C. B LAYOUT

Needle Length 10.5(mm)

Unless Otherwise Specified		1.27mm Pin Header, Single Row RightAngle		上海洲日电子有限公司 Shanghai Zhouri Electronics CO.,LTD 上海康司玛电子设备进出口有限公司 Shanghai KangSiMa Eletronic Equipment import and export Co.,LTD	
Dimension	Tolerance	Version Number	20140718 A/0		
	Decimal	Drawing Number	ZR20140718-006		
X.	±0.3	REV	A	Scale	1:1
X.X	±0.2			Unit	mm
X.XX	±0.15			A4	
Designed	Ma Chao	The Third Angle Projection		Sheet Of Pages	
Checked	Li zhen				
Approved	Fan Hao Hua				