



材料Material
 原料Insulator: PA6T, (UL 94V-0)
 相关材料Related Material: Brass
 表面涂层Surface Coating: Gold Over Nickel

规格Specification
 额定电流Current rating: 1AMP
 耐压Dielectric Withstanding Voltage: 500v Ac Min
 绝缘电阻Insulation Resistance: 1000MΩ min
 接触电阻Contact resistance: 30MΩ Max
 工作温度Operating Temperature: -45℃~+105℃

Order Information:

02	X	XX	X	XX/XXX	XX	X	XX
Plastics Height 1.H=2.54mm 2.H=2.0mm 3.H=1.0mm	NO.of Pins Per Row 1X40 1-40	Connector Type I=Straight L=Right Angle S=S.M.T	Pin Length XX=C+D+H XXX=C+D+H+E	Contact Plating 100=G/F 0.8u" 101=1u" 102=3u" 103=5u"	Insulator Material Option A: BK-PBT B: BK-PA66 C: BK-PA6T D: BK-PA46 E: BK-LCP F: Special	Space 01=2.54mm 02=2.0mm 03=1.27mm	

P. C. B LAYOUT

Needle Length 10.5/13(mm)

Unless Otherwise Specified		1.27mm Pin Header, Dual Row RightAngle		上海洲日电子有限公司 Shanghai Zhouri Electronics CO.,LTD 上海康司玛电子设备进出口有限公司 Shanghai KangSiMa Eletronic Equipment import and export Co.,LTD	
Dimension	Tolerance	Version Number	20140718 A/1	Drawing Number ZR20140718-014	
	Decimal	Scale	1:1	Unit	mm
X.	±0.3	Angle	±5°	A4	
X.X	±0.2	The Third Angle Projection		Sheet Of Pages	
X.XX	±0.15				
Designed	Ma Chao				
Checked	Li zhen				
Approved	Fan Hao Hua				