



材料Material

原料Raw material:PA46,(UL 94V-0)

相关材料Related Material: Brass

表面涂层Surface Coating:Gold Over Nickel

规格Specification

额定电流Current rating:1.5AMP

耐压Dielectric Withstanding Voltage:500v Ac Min

绝缘电阻Insulation Resistance:1000MΩ min

接触电阻Contact resistance:30MΩ Max

工作温度Operating Temperature:-45℃~+105℃

Order Information:

03 XX X XX X XX

NO.of Ppins Per Row 2-100	Connector Type I=Straight L=Right Angle S=S.M.T	Contact Plating 100=G/F 0.8u" 101=1u" 102=3u" 103=5u"	Material Option A: BK-PBT B: BK-PA66 C: BK-PA6T D: BK-PA46 E: BK-LCP F: Special	Spacing 01=2.54mm 02=2.0mm 03=1.27mm
---------------------------------	--	---	---	---

Unless Otherwise Specified			2.00mm Female Header , Dual Row , S.M.T		上海洲日电子有限公司						
Dimension	Tolerance		Drawing Number		Shanghai Zhouri Electronics CO.,LTD						
	Decimal	Angle						20140718 A/0			
X.	±0.3	±5°	Version Number		Shanghai KangSiMa Eletronic Equipment import and export Co.,LTD						
X.X	±0.2	±3°						ZR20140718-PM-08			
X.XX	±0.15		Designed	Ma Chao	REV	A	Scale	1:1	Unit	mm	A4
			Checked	Li zhen	The Third Angle Projection						Sheet Of Pages
			Approved	Fan Hao Hua							