



材料Material
 原料Raw material: PA46, (UL 94V-0)
 相关材料Related Material: Brass
 表面涂层Surface Coating: Gold Over Nickel

规格Specification
 额定电流Current rating: 1.5AMP
 耐压Dielectric Withstanding Voltage: 500v Ac Min
 绝缘电阻Insulation Resistance: 1000MΩ min
 接触电阻Contact resistance: 30MΩ Max
 工作温度Operating Temperature: -45℃ ~ +105℃

Order Information:

03 XX X XX X XX

NO. of Pins Per Row 2X22 4-44	Connector Type I= Straight L= Right Angle S= S.M.T	Contact Plating 100=G/F 0.8u" 101=1u" 102=3u" 103=5u"	Material Option A: BK-PBT B: BK-PA66 C: BK-PA6T D: BK-PA46 E: BK-LCP F: Special	Spacing 01=2.54mm 02=2.0mm 03=1.27mm
-------------------------------------	---	---	---	---

Unless Otherwise Specified		2.00mm Female Header , Dual Row , Right Angle		上海洲日电子有限公司 Shanghai Zhouri Electronics CO.,LTD		
Dimension	Tolerance			上海康司玛电子设备进出口有限公司 Shanghai KangSiMa Eletronic Equipment import and export Co.,LTD		
	Decimal	Angle	Drawing Number	20140718 A/0		
X.	±0.3	±5°	Version Number	ZR20140718-PM-16		
X.X	±0.2	±3°	REV	A	Scale	1:1
X.XX	±0.15		The Third Angle Projection		Unit	mm
Designed	Ma Chao			A4		
Checked	Li zhen			Sheet Of Pages		
Approved	Fan Hao Hua					